GRÜNIG · SWITZERLAND

GRÜNIG G-STRETCH 215

PRE-PRESS / SCREEN STRETCHING / MANUAL



OVERVIEW

The pneumatic G-STRETCH 215 machine allows reaching the maximum stretching values for all types of meshes, with utmost precision.

BRAND	Grünig
COUNTRY	Switzerland
MODEL	G-STRETCH 215
SERIES	G-STRETCH
CATEGORY	Pre-press
TYPE	Screen stretching
OPERATION	Manual

01 SPECIFICATIONS

G-STRETCH 215	
SB screen width	750-3000 mm
SL screen length	750-3000 mm
Frame profile thickness	20-70 mm
Travel distance p.clamp	115 mm
Length	(2xSL)+80 mm/inch
Width	(2xSB)+80 mm/inch
Height	860 mm/inch
Pressure	9 Bar
Air consumption	5 -15 lt/min
Permanent sound pressure level	<70 dB (A)

G-STRETCH 215A	
SB screen width	750-3000 mm
SL screen length	750-3000 mm
Frame profile thickness	20-50 mm
Travel distance per clamp	115 mm
Length	(2xSL)+80 mm
Width	(2xSB)+80 mm
Height	860 mm
Voltage	1x230+N+PE | 1x110+N+Pe V
Frequency	50-60 Hz
Pressure	9 Bar
Consumption	5-15 lt/min
Permanent sound pressure level	<70 dB (A)

02 FEATURES

- Maximum frame format 3000 x 3000 mm / 118 x 118 inch
- Instant adjustment of the machine size
- Automatic pre-bowing of the screen frames
- Pneumatic two-circuit control panel
- No contact between frame and mesh during stretching process
- Pneumatic stretching with highest precision/reproducibility

03 APPLICATIONS

Pneumatic stretching of frames up to 3000 x 3000 mm

Maximum stretching values for all types of meshes

SUPPLIED IN INDIA BY SUNSTAR GRAPHICS

Installation, operator training, spares and service from Mumbai.

Send your material, print size and volume per hour for a quotation in rupees.

+91 98203 61705 · SALES@SUNSTARGRAPHICS.COM

PRODUCT PAGE

Specifications are taken from the manufacturer's published data and may change. Confirm the configuration for your job with Sunstar before ordering.