GRÜNIG · SWITZERLAND

GRÜNIG G-STRETCH 270

PRE-PRESS / SCREEN STRETCHING / FULLY AUTOMATIC



OVERVIEW

The G-STRETCH 270 allows stretching all your meshes with the highest possible degree of precision, in true alignment with the thread and with the desired stretching values.

BRAND	Grünig
COUNTRY	Switzerland
MODEL	G-STRETCH 270
SERIES	G-STRETCH
CATEGORY	Pre-press
TYPE	Screen stretching
OPERATION	Fully automatic

01 SPECIFICATIONS

G-STRETCH 270	
SB screen width	1250+2000 mm
SL screen length	1250+2000 mm
Frame profile thickness	20-70 mm
Travel distance per clamp	100 mm
Length	(2xSL)+355 mm
Width	(2xSB)+355 mm
Height	1140 mm
Voltage	1x230+N+PE | 2x220+PE V
Frequency	50/60 Hz
Pressure	7 Bar
Consumption	5-15 L/min
Permanent sound pressure level	<70 dB (A)

G-STRETCH 270 A	
SB screen width	1250+2000 mm
SL screen length	1250+2000 mm
Frame profile thickness	20-70 mm
Travel distance per clamp	100 mm
Length	(2xSL)+355 mm
Width	(2xSB)+355 mm
Height	1140 mm
Voltage	1x230+N+PE | 2x220+PE V
Frequency	50/60 Hz
Pressure	7 Bar
Consumption	5-15 l/min
Permanent sound pressure level	<70 dB (A)

G-STRETCH 270 UV-BOND LED	
Frame width (SB)	1250 - 2000 mm
Frame length (SL)	1250 - 2000 mm
Frame profile height	20 - 70 mm
Width	2xSB+310 mm
Length	2xSL+590 mm
Height	2425 mm
Travel distance per clamp	100 mm

Specifications are taken from the manufacturer's published data and may change. Confirm the configuration for your job with Sunstar before ordering.

Electric	230 V / 50 Hz (L+N+PE) | 220 V / 60 Hz (2L+PE)	IT-Network	Ethernet / RJ45
Compressed air	1/4" / 6 bar / 10 l/min	Continuous sound pressure level	<70 dB (A)

02 FEATURES

- Automatic stretching mechanism operating with the G-CHECK 2 measuring instrument from the lower mesh side
- Telescopic and progressively adjustable size adjustment
- Stretching in true alignment with the thread, without any mesh distortion
- Optimal handling and highest degree of precision
- Automatic frame pre-bowing
- No contact between the mesh and the frame during stretching

03 APPLICATIONS

Automatic stretching in true alignment with the thread

Multiple handling of small frames (option support table)

SUPPLIED IN INDIA BY SUNSTAR GRAPHICS

Installation, operator training, spares and service from Mumbai.

Send your material, print size and volume per hour for a quotation in rupees.

+91 98203 61705 · SALES@SUNSTARGRAPHICS.COM

PRODUCT PAGE

Specifications are taken from the manufacturer's published data and may change. Confirm the configuration for your job with Sunstar before ordering.