GRÜNIG · SWITZERLAND

GRÜNIG G-STRETCH 281

PRE-PRESS / SCREEN STRETCHING / FULLY AUTOMATIC



OVERVIEW

The G-STRETCH 281 BASIC enables you to reduce mesh costs, to stretch with utmost speed and flexibility while keeping expenses under control.

BRAND	Grünig
COUNTRY	Switzerland
MODEL	G-STRETCH 281
SERIES	G-STRETCH
CATEGORY	Pre-press
TYPE	Screen stretching
OPERATION	Fully automatic

01 SPECIFICATIONS

G-STRETCH 281	
SB stretching width	1500-4000 mm
SL stretching length	2000-10000 mm
Frame profile thickness	30-120 mm
Width	SB + 810
Length	SL + 1415
Height	1040
Voltage	1x230 + N + PE | 3x220 + PE V
Frequency	50/60 Hz
Note	Compressed air Only required for options G1 or G2
Pressure	6 Bar
Consumption	0.6 m3/h
Permanent sound pressure level	< 70 dB (A)

G-STRETCH 281A	
SB stretching width	1500 - 4000 mm
SL stretching length	2000 - 10000 mm
Frame profile thickness	30 - 120 mm
Width	SB + 810 mm
Length	SL + 1415 mm
Height	1040 mm
Voltage	1x230 + N + PE | 2x220 + PE V
Frequency	50/60 Hz
Note	Compressed air only required for options G1 or G2
Pressure	6 Bar
Air consumption	0.6 m3/h

02 FEATURES

- For maximum stretching surface 4000 x 10000 mm / 157 x 394 inch
- High yield with a minimum of mesh consumption
- Remote control for all the stretching functions
- Adjustable stretching speeds for warp and weft directions
- No contact between frame and mesh during stretching process
- Easy setting of the desired stretching angle

03 APPLICATIONS

Large-surface stretching up to 4000 x 10000 mm

Simultaneous handling of several screen frames

SUPPLIED IN INDIA BY SUNSTAR GRAPHICS

Installation, operator training, spares and service from Mumbai.

Send your material, print size and volume per hour for a quotation in rupees.

+91 98203 61705 · SALES@SUNSTARGRAPHICS.COM

PRODUCT PAGE

Specifications are taken from the manufacturer's published data and may change. Confirm the configuration for your job with Sunstar before ordering.