LUEN CHEONG · HONG KONG

# LUEN CHEONG SD3000

DRYERS / IR AND HOT-AIR DRYERS




OVERVIEW

Our IR Drying Tunnel is engineered to provide efficient and consistent curing for a wide range of thermosetting inks used in screen printing, pad printing, and spraying applications.

| | |
|---|---|
| BRAND | Luen Cheong |
| COUNTRY | Hong Kong |
| MODEL | SD3000 |
| SERIES | SD |
| CATEGORY | Dryers |
| TYPE | IR and hot-air dryers |

## 01 SPECIFICATIONS

| | |
|---|---|
| Conveyor length | 3000 mm |
| Conveyor width | 600 mm |
| Machine size (LxWxH) | (3100 x 1050 x 1260) mm |
| Entrance Height | 120 mm |
| Working power | AC 380V 50Hz |
| Temperature Adjustment Range | 0-200 °C |
| Constant Temperature Accuracy | ±2 °C |
| Temperature resolution | 1 °C |
| Belt speed adjustment | 0-10 M/MIN |
| Package Dimensions (LxWxH) | 318 x 99 x 128 cm |
| Gross weight | 438 KG |

## 02 FEATURES

- Intelligent temperature control for stable curing
- Hot circulating system reduces energy consumption
- Adjustable belt speed and tunnel temperature
- Solidifies heat-set and special printing inks
- Teflon screen belt for longevity

## 03 APPLICATIONS

Screen printing · Pad printing · Spraying thermosetting inks · Heat presses · Electric products · Silicon components · Electric membrane keypads · Window glass · Electronics manufacturing · Automotive parts printing · Textile printing · Promotional product decoration · Glass printing

## SUPPLIED IN INDIA BY SUNSTAR GRAPHICS

Installation, operator training, spares and service from Mumbai.

Send your material, print size and volume per hour for a quotation in rupees.

+91 98203 61705 · SALES@SUNSTARGRAPHICS.COM

PRODUCT PAGE



Specifications are taken from the manufacturer's published data and may change. Confirm the configuration for your job with Sunstar before ordering.